



7210 C – 5th  
Street SE Calgary,  
Alberta T2H 2L9

**Technical Data Sheet**

Bus: 403-216-3300  
Fax: 403-216-3306  
www.temprotec.com

## TEFLON COATED FABRIC EJ1650

<b>TEMPERATURE RESISTANCE CONTINUOUS USE</b>	<b>600° F</b>
<b>BASE FABRIC</b>	FIBERGLASS
<b>COLOR AND COATING</b>	GREY / PTFE
<b>WEIGHT</b>	16.5 oz / yd <sup>2</sup> +/- 10%
<b>THICKNESS</b>	0.017" +/- 10%
<b>TENSILE STRENGTH</b>	WARP 410 x FILL 355 lbs / in
<b>SIZE</b>	60" x 50 lyds <span style="float: right;">95 lbs</span>
<b>ADVANTAGES</b>	<ul style="list-style-type: none"><li>• EXCELLENT CHEMICAL RESISTANCE</li><li>• EXCELLENT TEMPERATURE EXPOSURE CAPABILITIES</li><li>• EASILY SEWN</li><li>• FLAME RETARDANT</li></ul>
<b>APPLICATIONS</b>	<ul style="list-style-type: none"><li>• REMOVABLE INSULATION PADS</li><li>• FLANGE, VALVE AND PUMP COVERS</li><li>• EQUIPMENT COVERS</li></ul>

*THE INFORMATION PRESENTED IS INTENDED AS A SPECIFICATION GUIDE ONLY. MATERIALS SHOULD BE TESTED FOR ITS SUITABILITY IN ANY APPLICATION. USERS SHOULD ALSO FAMILIARIZE THEMSELVES WITH THE MSDS BEFORE HANDLING. NO WARRANTIES ARE EXPRESSED OR IMPLIED AS APPLICATION CONDITIONS ARE BEYOND OUR CONTROL*