



7210 C – 5th
Street SE Calgary,
Alberta T2H 2L9

Technical Data Sheet

Bus: 403-216-3300
Fax: 403-216-3306
www.temprotec.com

FIBERGLASS BRAIDED SLEEVING

| | |
|-------------------------------|-------------------------------------|
| TEMPERATURE RESISTANCE | 1000°F |
| CONTENT | 100% TYPE E FIBERGLASS YARNS |
| WEAVE | PLAIN |
| WALL THICKNESS | 1/16" Standard (1/8" by request) |

SIZE (ID) 1/4" THROUGH 4"

APPLICATIONS RECOMMENDED AS SLEEVING FOR COPPER OR ALUMINUM TUBING,
ELECTRICAL APPLIANCE LOADS AND CABLES, AND OTHER CONDUCTORS.

- FEATURES**
- PROVIDES THERMAL AND INSULATION PROTECTION
 - ABRASION RESISTANT
 - CHEMICAL RESISTANT
 - LIGHTWEIGHT
 - FLEXIBLE
 - HIGH TENSILE STRENGTH

THE INFORMATION PRESENTED IS INTENDED AS A SPECIFICATION GUIDE ONLY. MATERIALS SHOULD BE TESTED FOR ITS SUITABILITY IN ANY APPLICATION. USERS SHOULD ALSO FAMILIARIZE THEMSELVES WITH THE MSDS BEFORE HANDLING. NO WARRANTIES ARE EXPRESSED OR IMPLIED AS APPLICATION CONDITIONS ARE BEYOND OUR CONTROL