



7210 C – 5th
Street SE Calgary,
Alberta T2H 2L9

Technical Data Sheet

Bus: 403-216-3300
Fax: 403-216-3306
www.temprotec.com

FIBERGLASS TAPES

TEMPERATURE RESISTANCE	1000°F
TYPE	PLAIN OR BOLT HOLE
CONTENT AND WEAVE	100% FIBERGLASS / PLAIN WEAVE
CHEMICAL RESISTANCE	Resists most acids, alkalis and solvents with the exception of hydrofluoric acid and corrosive environments at elevated temperatures
SPECIFICATIONS	MIL-Y-1140, MIL-C-20079
SIZES AVAILABLE	
1/16" (0.06")	1/2" THROUGH 6" x 100 FT ROLLS
1/8" (0.125")	1/2" THROUGH 6" x 100 FT ROLLS
1/4" (0.25")	1" THROUGH 4" x 50 FT ROLLS

NOTE: PRESSURE SENSITIVE (300 F) AND STAINLESS STEEL INSERT TAPES ARE AVAILABLE UPON REQUEST.

THE INFORMATION PRESENTED IS INTENDED AS A SPECIFICATION GUIDE ONLY. MATERIALS SHOULD BE TESTED FOR ITS SUITABILITY IN ANY APPLICATION. USERS SHOULD ALSO FAMILIARIZE THEMSELVES WITH THE MSDS BEFORE HANDLING. NO WARRANTIES ARE EXPRESSED OR IMPLIED AS APPLICATION CONDITIONS ARE BEYOND OUR CONTROL