



7210 C – 5th
Street SE Calgary,
Alberta T2H 2L9

Technical Data Sheet

Bus: 403-216-3300
Fax: 403-216-3306
www.temprotec.com

GASKET GLUE

PRODUCT CHARACTERISTICS

- WATER-BASED
- SUPERIOR ADHESION
- **1500°F** RATING
- APPLICATOR TO AVOID EXCESSIVE GLUE
- EXCESSIVE THICKNESS CAN LEAD TO PREMATURE CRACKING AND SEPARATION

APPLICATIONS

- GLUING REPLACEMENT OR EXISTING FIBERGLASS GASKETS TO METAL SURFACE
- GLUING SECTIONED DRY PACK COMBUSTION CHAMBERS

PACKAGING

- 24ea – 2 fl.oz. BOTTLES WITH YORKER TIP

CARTON SIZE

- 9 – 1/8" x 7 – 5/8" x 4 – 9/16"

WEIGHT

- 4 lbs

NOTE: GASKET GLUE IS A VISCOUS PRODUCT THAT WILL WITHSTAND HEAT IN EXCESS OF FIBERGLASS GASKETS. ONCE CURED BY HEAT OR AIR EXPOSURE, THE GLUE BECOMES ROCK HARD AND CAN ONLY BE REMOVED BY PHYSICAL MEANS.

THE INFORMATION PRESENTED IS INTENDED AS A SPECIFICATION GUIDE ONLY. MATERIALS SHOULD BE TESTED FOR ITS SUITABILITY IN ANY APPLICATION. USERS SHOULD ALSO FAMILIARIZE THEMSELVES WITH THE MSDS BEFORE HANDLING. NO WARRANTIES ARE EXPRESSED OR IMPLIED AS APPLICATION CONDITIONS ARE BEYOND OUR CONTROL.