

## HOOK & LOOP VELCRO

### DESCRIPTION

- 100 % Polyester woven Hook & Loop Fastener Tape
- A tough, lightweight abrasion-resistant polymer with excellent durability
- Nylon performs well in high temperatures (maximum continued use temperature range of 270 to 300 degrees F)

### COLOR AND SIZES AVAILABLE

BLACK, GREY & DARK GREY  
AVAILABLE IN 1" AND 2" WIDE

### SHEAR STRENGTH TEST

- CNS 12649-3.5:1989, Test overlap length 50mm, Speed:300mm/min. Average value:1.24kgf/cm<sup>2</sup>

### PEEL STRENGTH TEST

- CNS 12679-3.6:1989, Test overlap length 50mm, Speed:300mm/min. Average value:376.85g/cm
- CNS 12679-3.7:1989

### SHEAR FATIGUE RESISTANCE TEST

- After 2000 cycles shear strength:102kgf/cm<sup>2</sup> (-18%)
- After 2000 cycles peel strength:240.36g/cm (-36%)

**THE INFORMATION PRESENTED IS INTENDED AS A SPECIFICATION GUIDE ONLY. MATERIALS SHOULD BE TESTED FOR ITS SUITABILITY IN ANY APPLICATION. USERS SHOULD ALSO FAMILIARIZE THEMSELVES WITH THE MSDS BEFORE HANDLING. NO WARRANTIES ARE EXPRESSED OR IMPLIED AS APPLICATION CONDITIONS ARE BEYOND OUR CONTROL.**