



7210 C – 5<sup>th</sup> Street SE  
Calgary, Alberta  
T2H 2L9

## Technical Data Sheet

Bus: 403-216-3300  
Fax: 403-216-3306  
www.temprotec.com

### SILFLEX 1750C

**UPPER USE TEMPERATURE  
(continuous)**

**480° F**

**249° C**

**DESCRIPTION**

SILICONE / FIBERGLASS COMPOSITE WITH PROVEN FLEXIBLE COATING TECHNOLOGY IS ENGINEERED FOR STANDARD DUTY INSULATION JACKETING APPLICATIONS

**COLOR**

GREY

**WEIGHT**

17 oz / yd<sup>2</sup>

577 g / m<sup>2</sup>

**THICKNESS**

0.017"

0.43 mm

**WIDTH**

60" (NOMINAL)

1524 MM

**TENSILE STRENGTH**

WARP: 350 lbs / in

3128 N / 50 mm

FILL: 300 lbs / in

2681 N / 50 mm

**FEATURES**

- SEVERE TEMPERATURE AND CHEMICAL EXPOSURE CAPABILITY
- FLAME RETARDANT
- EASILY SEWN
- SUCCESSFULLY USED IN INSULATION JACKETING APPLICATIONS SINCE 1985

THE INFORMATION PRESENTED IS INTENDED AS A SPECIFICATION GUIDE ONLY. MATERIALS SHOULD BE TESTED FOR ITS SUITABILITY IN ANY APPLICATION. USERS SHOULD ALSO FAMILIARIZE THEMSELVES WITH THE MSDS BEFORE HANDLING. NO WARRANTIES ARE EXPRESSED OR IMPLIED AS APPLICATION CONDITIONS ARE BEYOND OUR CONTROL.