



7210 C – 5th
Street SE Calgary,
Alberta T2H 2L9

Technical Data Sheet

Bus: 403-216-3300
Fax: 403-216-3306
www.temprotec.com

SILICA TAPE

TEMPERATURE RESISTANCE

STANDARD TAPES **1800° F** continuous
IRISH TAPE **2300° F***

COMPOSITION SILICA (>96%)

AVAILABILITY 100 lineal feet +/-10% / roll

SLIT TAPE PROPERTIES

PRODUCT	PRODUCT CODE	NOMINAL THICKNESS	NOMINAL WIDTH
Standard Tape (with adhesive)	UT48-2	0.026"	2"
	UT48-4	0.026"	4"
	UT96-2	0.050"	2"
	UT96-4	0.050"	4"
ABRASION RESISTANT TAPE (no adhesive, sealed edges)	AR48-2	0.033"	2"
	AR48-4	0.033"	4"
	AR96-2	0.060"	2"
	AR96-4	0.060"	4"
IRISH TAPE (no adhesive, sealed edges)	2221-96-2	0.052"	2"
	2221-96-4	0.052"	4"

* Irish extends the stability and flexible characteristics of standard slit tapes to 2300°F. High excursion temperatures over 2000°F may cause embrittlement, but the tape continues to insulate.

THE INFORMATION PRESENTED IS INTENDED AS A SPECIFICATION GUIDE ONLY. MATERIALS SHOULD BE TESTED FOR ITS SUITABILITY IN ANY APPLICATION. USERS SHOULD ALSO FAMILIARIZE THEMSELVES WITH THE MSDS BEFORE HANDLING. NO WARRANTIES ARE EXPRESSED OR IMPLIED AS APPLICATION CONDITIONS ARE BEYOND OUR CONTROL.