

SILVERFLEX 910 SF

TEMPERATURE RESISTANCE	- 415°F to + 600°F	FED SPEC HHB-100B
MATERIAL DESCRIPTION	Manufactured from PTFE impregnated fiberglass	
WEIGHT	15.8 oz / yd²	ASTM-D-3776-96
THICKNESS	0.010"	ASTM-D-1777-96
TENSILE STRENGTH W x F	200 x 150 lbs / inch	ASTM-D-5035-95
DIELECTRIC STRENGTH	750 Volts / Mil	ASTM-D-149-95a

PTFE ADVANTAGES

- Super smooth
- Low friction
- Non-stick surface
- Exceptional dielectric properties
- High tensile strength
- Superior chemical resistance
- Expansive operational temperature range

APPLICATIONS

- Thermal insulation for very high temperature environments
- Gaskets and seals for harsh chemical environments

THE INFORMATION PRESENTED IS INTENDED AS A SPECIFICATION GUIDE ONLY. MATERIALS SHOULD BE TESTED FOR ITS SUITABILITY IN ANY APPLICATION. USERS SHOULD ALSO FAMILIARIZE THEMSELVES WITH THE MSDS BEFORE HANDLING. NO WARRANTIES ARE EXPRESSED OR IMPLIED AS APPLICATION CONDITIONS ARE BEYOND OUR CONTROL