



7210 C – 5th  
Street SE Calgary,  
Alberta T2H 2L9

**Technical Data Sheet**

Bus: 403-216-3300  
Fax: 403-216-3306  
www.temprotec.com

## TECGLASS® 1300GL Black



ANSI/FM 4950 \*  
WELDING CURTAINS

TEMPERATURE RESISTANCE **1000° F**

|                |  |          |
|----------------|--|----------|
| CONTENT        | 100% FIBERGLASS YARNS  |          |
| WEAVE          | 4 HARNESS SATIN  |          |
| WEIGHT         | 13 oz / yd <sup>2</sup>  |          |
| THICKNESS      | 0.016"   |          |
| COLOR          | BLACK  |          |
| COUNT          | WARP: 48   | FILL: 31 |
| FABRIC FINISH  | PLAIN OR 9383 (HEAT CLEANED)   |          |
| SPECIFICATIONS | ALL UNCOATED FIBERGLASS YARNS MEET USCG 164.009<br>"TEST FOR INCOMBUSTIBILITY" |          |
| SIZE           | 60" x 50 lyds  |          |

**\* NOTE: WELDING PADS AND WELDING BLANKETS MAY ALSO BE USED AS WELDING CURTAINS.**

TecGlass® is a registered trademark of Tempro Tec Inc.

*THE INFORMATION PRESENTED IS INTENDED AS A SPECIFICATION GUIDE ONLY. MATERIALS SHOULD BE TESTED FOR ITS SUITABILITY IN ANY APPLICATION. USERS SHOULD ALSO FAMILIARIZE THEMSELVES WITH THE MSDS BEFORE HANDLING. NO WARRANTIES ARE EXPRESSED OR IMPLIED AS APPLICATION CONDITIONS ARE BEYOND OUR CONTROL.*