



7210 C – 5th  
Street SE Calgary,  
Alberta T2H 2L9

## Technical Data Sheet

Bus: 403-216-3300  
Fax: 403-216-3306  
www.temprotec.com

# TECGLASS® GL 2025/9383



ANSI/FM 4950 \*  
WELDING CURTAINS

TEMPERATURE RESISTANCE **1000° F**

<b>CONTENT</b>	<b>100% FIBERGLASS YARNS</b>	
<b>WEAVE</b>	<b>PLAIN</b>	
<b>WEIGHT</b>	<b>18.0 oz / yd<sup>2</sup></b>	
<b>THICKNESS</b>	<b>0.036"</b>	
<b>COLOR</b>	<b>BEIGE</b>	
<b>COUNT</b>	<b>WARP: 19</b>	<b>FILL: 14</b>
<b>FABRIC FINISH</b>	<b>PLAIN OR 9383 (HEAT CLEANED) **</b>	
<b>USCG SPECIFICATIONS</b>	<b>164.009 "TEST FOR INCOMBUSTIBILITY"</b>	
<b>MILITARY SPECIFICATIONS (FINISH)</b>	<b>MIL C 20079H TYPE 1 CLASS 9 (WITH 9383)</b>	
<b>SIZE</b>	<b>40" &amp; 60" x 50 lyds</b>	
<b>FEATURES</b>	<b>TECGLASS® IS SAFE, TOUGH AND VERSATILE</b>	

**\*\* HEAT CLEANED (9383) MATERIAL HAS BEEN APPROVED AS A WELDING CURTAIN UNDER FM APPROVAL STANDARD 4950 FOR HOT WORK PROTECTION**

**\* NOTE: WELDING PADS AND WELDING BLANKETS MAY ALSO BE USED AS WELDING CURTAINS.**

TecGlass® is a registered trademark of Temprow Tec Inc.

**THE INFORMATION PRESENTED IS INTENDED AS A SPECIFICATION GUIDE ONLY. MATERIALS SHOULD BE TESTED FOR ITS SUITABILITY IN ANY APPLICATION. USERS SHOULD ALSO FAMILIARIZE THEMSELVES WITH THE MSDS BEFORE HANDLING. NO WARRANTIES ARE EXPRESSED OR IMPLIED AS APPLICATION CONDITIONS ARE BEYOND OUR CONTROL**