TEMPRO TEC® Inc.
7210 C – 5th Street SE Calgary, Alberta T2H 2L9

Technical Data Sheet

Bus: 403-216-3300
Fax: 403-216-3306
www.temprotec.com

TECPRENE® 2025 GLN

FM C US APPROVED

ANSI/FM 4950 * WELDING CURTAINS

TEMPERATURE RESISTANCE

BASE FABRIC	**1000° F**
COATING	**225° F**

BASE FABRIC CONTENT	**100% FIBERGLASS YARNS**
WEAVE	**PLAIN**
BASE FABRIC WEIGHT	**18.0 oz / yd^2**
BASE FABRIC THICKNESS	**0.030”**
FINISHED FABRIC WEIGHT	**21.0 oz / yd^2**
COUNT	**WARP: 19 FILL: 14**
FABRIC FINISH	**COMPOUNDED NEOPRENE RUBBER USED ON ONE SIDE OF THE CLOTH AND THE OTHER SIDE DYED A LIGHT YELLOW (OTHER COLORS AVAILABLE ON REQUEST). USED TO EASE FABRICATION AND INCREASE ABRASION RESISTANCE.**
SIZE	**40” & 60” x 50 lyds**

NOTE: Must be used in well ventilated area.

*** NOTE: WELDING PADS AND WELDING BLANKETS MAY ALSO BE USED AS WELDING CURTAINS.**

TecPrene® is a registered trademark of Tempro Tec Inc.

THE INFORMATION PRESENTED IS INTENDED AS A SPECIFICATION GUIDE ONLY. MATERIALS SHOULD BE TESTED FOR ITS SUITABILITY IN ANY APPLICATION. USERS SHOULD ALSO FAMILIARIZE THEMSELVES WITH THE MSDS BEFORE HANDLING.

NO WARRANTIES ARE EXPRESSED OR IMPLIED AS APPLICATION CONDITIONS ARE BEYOND OUR CONTROL.

© Copyright 2010 Tempro Tec® Inc