



7210 C – 5th
Street SE Calgary,
Alberta T2H 2L9

Technical Data Sheet

Bus: 403-216-3300
Fax: 403-216-3306
www.temprotec.com

TECSTAR[®] TAPE

TEMPERATURE RESISTANCE	Fabric is rated at 1000°F continuous, remains stable to 1500°F with vermiculite coating
CONTENT AND WEAVE	100% FIBERGLASS YARNS / PLAIN
TAPE FINISH	Vermiculite is an inorganic, chemically inert, noncombustible and odorless coating
TYPE	PLAIN OR BOLT HOLE
NOMINAL THICKNESS	0.125"
STANDARD LENGTH	100 ft / roll
STANDARD NOMINAL WIDTHS **	1/2", 5/8", 3/4", 1", 1-1/2", 2", 2-1/2", 3", 4", 5", 6", 7"
NOTE:	Available with a high performance pressure sensitive adhesive <ul style="list-style-type: none">• Adhesive temperature resistance: 300°F• Adhesive is only used to aid the installation process. After the material is in place, it is usually mechanically bonded so that the adhesive is no longer necessary

** Width of finished product may be narrower due to shrinkage during coating.

TecStar[®] is a registered trademark of Tempro Tec Inc.

THE INFORMATION PRESENTED IS INTENDED AS A SPECIFICATION GUIDE ONLY. MATERIALS SHOULD BE TESTED FOR ITS SUITABILITY IN ANY APPLICATION. USERS SHOULD ALSO FAMILIARIZE THEMSELVES WITH THE MSDS BEFORE HANDLING. NO WARRANTIES ARE EXPRESSED OR IMPLIED AS APPLICATION CONDITIONS ARE BEYOND OUR CONTROL.