

TECWELD® RSL SILICONE CLOTH



ANSI/FM 4950 *
WELDING CURTAINS

TEMPERATURE RESISTANCE

BASE FABRIC (CONTINUOUS)	1000° F
COATING (CONTINUOUS)	500° F

BASE FABRIC AND WEAVE COLOR AND COATING

FIBERGLASS / PLAIN WEAVE
RED / SILICONE

WEIGHT

14 oz / yd² +/- 10%

THICKNESS

0.013" +/- 10%

COUNT

WARP: 28

FILL: 20

SIZE

38" & 60" x 50"

TENSILE STRENGTH W x F

175 x 150 lbs / in

FTMS 191A/M5102

TEAR STRENGTH W x F

35 x 25 lbs

FTMS 191A/M5136

BURST STRENGTH

175 lbs / in²

FTMS191A/M5122 (MULLEN)

FTMS 191A/M5903.1

FLAME RESISTANCE

CHAR LENGTH	0.3 inch
AFTERGLOW	1 3 seconds

HYDROSTATIC RESISTANCE

200 lbs / in²

FTMS 191A/M5512 (MULLEN)

FEATURES

TecWeld® RSL is a fiberglass base fabric which has been coated with a specially formulated silicone rubber compound. The silicone coating adds extended life while providing greater oil and water resistance than uncoated fabrics as well as low smoke and flame retardancy.

*** NOTE: WELDING PADS AND WELDING BLANKETS MAY ALSO BE USED AS WELDING CURTAINS.**

TecWeld® is a registered trademark of Tempro Tec Inc.

THE INFORMATION PRESENTED IS INTENDED AS A SPECIFICATION GUIDE ONLY. MATERIALS SHOULD BE TESTED FOR ITS SUITABILITY IN ANY APPLICATION. USERS SHOULD ALSO FAMILIARIZE THEMSELVES WITH THE MSDS BEFORE HANDLING.
NO WARRANTIES ARE EXPRESSED OR IMPLIED AS APPLICATION CONDITIONS ARE BEYOND OUR CONTROL.