

3200SA SILICONE IMPREGNATED FABRIC

TEMPERATURE RESISTANCE	-65°F to 500°F	
BASE FABRIC AND WEAVE	FIBERGLASS / SATIN WEAVE	
COLOR AND COATING	GREY / SILICONE RUBBER	
WEIGHT	17 oz / yd ² +/- 10 %	ASTM-D-3776-96
THICKNESS	0.016" +/- 0.001"	ASTM-D-1777-96
TENSILE STRENGTH W x F	275 x 225 lbs / in	ASTM-D-5034-95
TEAR STRENGTH W x F	40 x 40 lbs	ASTM-D-5587-96
BURST STRENGTH ABRASION	600 psi	ASTM-D-3786-87
RESISTANCE	CS-10 Wheels, 500g load 500 revs, 15% weight loss max.	ASTM-D-3389-94
FLAME RESISTANCE	CHAR LENGTH 1 inch MAX. AFTERGLOW 1 second MAX. FLAME OUT 1 second MAX.	FED 191/5903.2
SIZE AND WEIGHT	60" x 50 lyds	95 lbs
ADVANTAGES	<ul style="list-style-type: none">• HIGHLY FLAME RETARDANT• HIGH TEMPERATURE RESISTANCE• SHEDS WATER AND CORROSIVE CHEMICALS	
APPLICATIONS	<ul style="list-style-type: none">• REMOVABLE INSULATION BLANKETS• EQUIPMENT COVERS• EXPANSION JOINTS• FLANGE COVERS	

THE INFORMATION PRESENTED IS INTENDED AS A SPECIFICATION GUIDE ONLY. MATERIALS SHOULD BE TESTED FOR ITS SUITABILITY IN ANY APPLICATION. USERS SHOULD ALSO FAMILIARIZE THEMSELVES WITH THE MSDS BEFORE HANDLING. NO WARRANTIES ARE EXPRESSED OR IMPLIED AS APPLICATION CONDITIONS ARE BEYOND OUR CONTROL