



7210 C – 5th Street SE
 Calgary, Alberta T2H 2L9

Technical Data Sheet

Bus: 403-216-3300
 Fax: 403-216-3306
 www.temprotec.com

TECGLASS® GL 2025/9383



ANSI/FM 4950 *
 WELDING CURTAINS

TEMPERATURE RESISTANCE	1000° F
CONTENT	100% FIBERGLASS YARNS
WEAVE	PLAIN
WEIGHT	18.0 oz / yd ²
THICKNESS	0.036"
COLOR	BEIGE
COUNT	WARP: 19 FILL: 14
FABRIC FINISH	PLAIN OR 9383 (HEAT CLEANED) **
USCG SPECIFICATIONS	164.009 "TEST FOR INCOMBUSTIBILITY"
MILITARY SPECIFICATIONS	MIL C 20079H TYPE 1 CLASS 9 (WITH 9383 FINISH)
SIZE	40" & 60" x 50 lyds
FEATURES	TECGLASS® IS SAFE, TOUGH AND VERSATILE

** HEAT CLEANED (9383) MATERIAL HAS BEEN APPROVED AS A WELDING CURTAIN UNDER FM APPROVAL STANDARD 4950 FOR HOT WORK PROTECTION

* NOTE: WELDING PADS AND WELDING BLANKETS MAY ALSO BE USED AS WELDING CURTAINS.

TecGlass® is a registered trademark of Tempro Tec Inc.

THE INFORMATION PRESENTED IS INTENDED AS A SPECIFICATION GUIDE ONLY. MATERIALS SHOULD BE TESTED FOR ITS SUITABILITY IN ANY APPLICATION. USERS SHOULD ALSO FAMILIARIZE THEMSELVES WITH THE MSDS BEFORE HANDLING. NO WARRANTIES ARE EXPRESSED OR IMPLIED AS APPLICATION CONDITIONS ARE BEYOND OUR CONTROL

