

GL 6000 – 40" PLAIN-WHITE FIBERGLASS CLOTH

TEMPERATURE RESISTANCE	1000° F
CONTENT AND WEAVE	100% FIBERGLASS YARNS / PLAIN
NOMINAL WEIGHT	60.0 oz / yd ²
NOMINAL THICKNESS	0.125"
COUNT	WARP: 10 FILL: 7
FABRIC FINISH	PLAIN OR 9383 (HEAT CLEANED)
NOMINAL WIDTH	40"
STANDARD COLOR	WHITE

ALL UNCOATED FIBERGLASS FABRICS ARE NON COMBUSTIBLE, MEETING USCG 164.009-5(f)

AVAILABLE WITH A HIGH PERFORMANCE PRESSURE SENSITIVE ADHESIVE

- ADHESIVE TEMPERATURE RESISTANCE: 300° F
- ADHESIVE IS ONLY USED TO AID THE INSTALLATION PROCESS, AFTER THE MATERIAL IS IN PLACE; IT IS USUALLY MECHANICALLY BONDED SO THAT THE ADHESIVE IS NO LONGER NECESSARY.

RAVEL RESISTANCE COATING AVAILABLE- SEE COATING SPEC SHEET FOR OPTIONS

NOTE: COATING FINISHES DECOMPOSE AT TEMPERATURES BELOW THE BASE FABRICS RESISTANCE.

THE INFORMATION PRESENTED IS INTENDED AS A SPECIFICATION GUIDE ONLY. MATERIALS SHOULD BE TESTED FOR ITS SUITABILITY IN ANY APPLICATION. USERS SHOULD ALSO FAMILIARIZE THEMSELVES WITH THE MSDS BEFORE HANDLING. NO WARRANTIES ARE EXPRESSED OR IMPLIED AS APPLICATION CONDITIONS ARE BEYOND OUR CONTROL.