

## HI TEMP CEMENT

<b>TEMPERATURE RESISTANCE</b>	<b>2100° F</b>
<b>STABILITY</b>	<b>CRACK AND SHRINK RESISTANT</b>
<b>COLOR</b>	<b>GREY</b>
<b>AVAILABILITY</b>	<b>3 lb., 6 lb., and 12 lb. plastic tubs 16 oz. cartridges</b>
<b>APPLICATIONS</b>	<ul style="list-style-type: none"><li>• <b>STOVES</b></li><li>• <b>FURNACES</b></li><li>• <b>BOILERS</b></li><li>• <b>FIREPLACES (ALL FUELS)</b></li><li>• <b>FLUE AND CHIMNEY JOINTS</b></li><li>• <b>BRICK LININGS</b></li><li>• <b>GASKETING</b></li><li>• <b>SEALS CRACKS AND JOINTS TO PREVENT SMOKE OR AIR LEAKS</b></li></ul>
<b>FEATURES</b>	<ul style="list-style-type: none"><li>• <b>NON-ASBESTOS</b></li><li>• <b>SPREADS EASILY</b></li><li>• <b>PRE-MIXED, READY TO USE</b></li></ul>

*THE INFORMATION PRESENTED IS INTENDED AS A SPECIFICATION GUIDE ONLY. MATERIALS SHOULD BE TESTED FOR ITS SUITABILITY IN ANY APPLICATION. USERS SHOULD ALSO FAMILIARIZE THEMSELVES WITH THE MSDS BEFORE HANDLING. NO WARRANTIES ARE EXPRESSED OR IMPLIED AS APPLICATION CONDITIONS ARE BEYOND OUR CONTROL.*