

INCONEL 600 SEWING THREAD

TEMPERATURE LIMIT	2000° F
WIRE	10 STRANDS 0.0017"
DIAMETER	Approx. 6,100 lft / lb
LUBRICANT	#4510 SILICONE
DIAMETER	0.0145"
BREAK STRENGTH	8 lbs
ELONGATION	30%

SPECIFICATIONS

AMS-5647
ASTM-A182
ASTM-A276FED-QQ-S-763
ASTM-A580
ASTM-A314MIL-S-23195
MIL-S-862
ASTM-A479

APPLICATIONS

- HIGH TEMPERATURE REMOVABLE AND REUSABLE INSULATION BLANKETS FOR MARINE, AEROSPACE, INDUSTRIAL AND COMMERCIAL INDUSTRIES.
- FIRE PROOFING PADS WHERE EXTREMELY HIGH TEMPERATURE RESISTANCE IS REQUIRED.

FEATURES

THE THREAD IS WOUND IN A UNIQUE FASHION AND COVERED WITH 3 FLAME RETARDENT POLYESTER THREADS TO PREVENT METAL TO METAL WEAR AND IS COATED WITH SILICONE FOR SMOOTH SEWING. MAINTAINS INTEGRITY AFTER LONG TERM EXPOSURE TO OUTSIDE ELEMENTS AND IS RESISTANT TO MILDEW, AGING, ALKALIS, CHLORIDES AND MANY OTHER LIQUIDS AND GASES.

THE INFORMATION PRESENTED IS INTENDED AS A SPECIFICATION GUIDE ONLY. MATERIALS SHOULD BE TESTED FOR ITS SUITABILITY IN ANY APPLICATION. USERS SHOULD ALSO FAMILIARIZE THEMSELVES WITH THE MSDS BEFORE HANDLING. NO WARRANTIES ARE EXPRESSED OR IMPLIED AS APPLICATION CONDITIONS ARE BEYOND OUR CONTROL.