

SGT -S2 / SS INSERT FIBERGLASS THREAD

TEMPERATURE RESISTANCE **1400° F****STYLE****SGT-18 S/S****SGT-24 S/S****COLOR**

NATURAL / TAN

NATURAL / TAN

DIAMETER

0.019"

0.023"

THREAD STYLES-2 GLASS FIBER WITH INTEGRAL TYPE 304 STAINLESS STEEL
WIRE**COATING**

PTFE

PTFE

YIELD

1975 yards / lb

1475 yards / lb

TENSILE STRENGTH

25 lbs

29 lbs

ADVANTAGES

- CHEMICAL RESISTANCE
- MINIMAL BUILDUP OF CONTAMINANTS
- EXCELLENT SEWABILITY
- THERMAL SHOCK RESISTANCE
- FLEXIBILITY TO **1400° F**
- MINIMIZE STRIP-BACK AND UNTWISTING

FEATURES

- EXTREME TEMPERATURE RESISTANCE
- HIGH TENSILE STRENGTH
- GOOD KNOT BREAKING STRENGTH
- UNIFORM PTFE COATING
- STAINLESS WIRE TWISTED IN
- HIGH TEMPERATURE STABILITY

THE INFORMATION PRESENTED IS INTENDED AS A SPECIFICATION GUIDE ONLY. MATERIALS SHOULD BE TESTED FOR ITS SUITABILITY IN ANY APPLICATION. USERS SHOULD ALSO FAMILIARIZE THEMSELVES WITH THE MSDS BEFORE HANDLING. NO WARRANTIES ARE EXPRESSED OR IMPLIED AS APPLICATION CONDITIONS ARE BEYOND OUR CONTROL