



7210 C – 5th
Street SE Calgary,
Alberta T2H 2L9

Technical Data Sheet

Bus: 403-216-3300
Fax: 403-216-3306
www.temprotec.com

TECSTAR® 18

TEMPERATURE RESISTANCE CONTINUOUS	1000° F	
	REMAINS STABLE TO 1500° F	WITH VERMICULITE COATING
BASE FABRIC AND WEAVE	100% FIBERGLASS / PLAIN	
COLOR AND COATING	BRONZE / VERMICULITE*	
BASE FABRIC WEIGHT	18 oz / yd ²	
BASE FABRIC THICKNESS	0.030"	
COUNT	WARP: 19	FILL: 14
SIZE	60" x 50 lyds	WIDTH OF PRODUCT MAY BE NARROWER DUE TO SHRINKAGE DURING COATING

*VERMICULITE IS AN INORGANIC, CHEMICALLY INERT, NON-COMBUSTIBLE & ODORLESS COATING

NOTE: MATERIAL SHOULD BE TESTED FOR ITS SUITABILITY IN ANY APPLICATION WHERE FLEXING OR VIBRATION OCCURS AT ELEVATED TEMPERATURES.

TecStar® is a registered trademark of Tempro Tec Inc.

THE INFORMATION PRESENTED IS INTENDED AS A SPECIFICATION GUIDE ONLY. MATERIALS SHOULD BE TESTED FOR ITS SUITABILITY IN ANY APPLICATION. USERS SHOULD ALSO FAMILIARIZE THEMSELVES WITH THE MSDS BEFORE HANDLING. NO WARRANTIES ARE EXPRESSED OR IMPLIED AS APPLICATION CONDITIONS ARE BEYOND OUR CONTROL

© Copyright 2010 Tempro Tec® Inc

