UC 100-96 SILICA CLOTH

TEMPERATURE RESISTANCE

CONTINUOUS USE 1800° F
MELT TEMPERATURE 3100° F

BASE FABRIC AND WEAVE SILICA – 8 HARNESS SATIN 96% min. silica content

COLOR CARAMEL

WEIGHT 36 oz / yd 2 +/- 10%

THICKNESS 0.056" +/- 10%

ABRASION RESISTANCE > 1000 cycles to failure (warp)

SIZE AND WEIGHT 36" x 50 lyds 100 lbs

CHLORIDE RESIDUAL 20 ppm

ADVANTAGES • HIGH STRENGTH AND ABRASION RESISTANCE

EASY TO FABRICATE

ALUMINUM AND SILICONE COATINGS AVAILABLE

APPLICATIONS

REMOVABLE INSULATION PADS

STRESS RELIEVING BLANKETS

• WELDING SCREENS AND CURTAINS

AUTOMOTIVE HEAT SHIELDS

• MUFFLERS AND SILENCERS

FIREPROOF BUILDING MATERIALS

FEATURES A heavyweight, high strength, acid-leached amorphous silica cloth that

is specially made to maximize both temperature resistance and room temperature physical strength. Meets MIL-C-24576A Type 1/Class1.

THE INFORMATION PRESENTED IS INTENDED AS A SPECIFICATION GUIDE ONLY. MATERIALS SHOULD BE TESTED FOR ITS SUITABILITY IN ANY APPLICATION. USERS SHOULD ALSO FAMILIARIZE THEMSELVES WITH THE MSDS BEFORE HANDLING. NO WARRANTIES ARE EXPRESSED OR IMPLIED AS APPLICATION CONDITIONS ARE BEYOND OUR CONTROL.