

NOMEX T-92 THREAD

NOMEX**92 - BONDED**

YIELD	6100 yds / lb	4620 yds / lb
MINIMUM TENSILE	5.0 lbs	6.9 lbs

SPECIFICATIONS MIL-T-43636A (FILAMENT) MIL-T-43636A (FILAMENT)

COLOR	SAGE GREEN	WHITE NATURAL
PACKAGING APPROX.	1 lb / SPOOL	1 lb / SPOOL

FEATURES

- EXTREMELY HEAT RESISTANT, DECOMPOSES AT **700°F**
- AFTER 1000 HOURS AT **425°F**, RETAINS 80% OF ORIGINAL STRENGTH
- EASIER TO USE THAN FIBERGLASS
- GOOD RESISTANCE TO MANY CHEMICALS, HIGHLY RESISTANT TO MOST HYDROCARBONS AND MANY OTHER ORGANIC SOLVENTS
- LIMITATIONS ARE UV RAYS, WHICH RESULT IN SOME LOSS OF STRENGTH OVER TIME

THE INFORMATION PRESENTED IS INTENDED AS A SPECIFICATION GUIDE ONLY. MATERIALS SHOULD BE TESTED FOR ITS SUITABILITY IN ANY APPLICATION. USERS SHOULD ALSO FAMILIARIZE THEMSELVES WITH THE MSDS BEFORE HANDLING. NO WARRANTIES ARE EXPRESSED OR IMPLIED AS APPLICATION CONDITIONS ARE BEYOND OUR CONTROL.