

TEFLON COATED FABRIC EJ1650

TEMPERATURE RESISTANCE CONTINUOUS USE	600° F
BASE FABRIC	FIBERGLASS
COLOR AND COATING	GREY / PTFE
WEIGHT	16.5 oz / yd ² +/- 10%
THICKNESS	0.015" +/- 10%
TENSILE STRENGTH	WARP 400 x FILL 300 lbs / in
SIZE	60" x 50 lyds 95 lbs
ADVANTAGES	<ul style="list-style-type: none">• EXCELLENT CHEMICAL RESISTANCE• EXCELLENT TEMPERATURE EXPOSURE CAPABILITIES• EASILY SEWN• FLAME RETARDANT
APPLICATIONS	<ul style="list-style-type: none">• REMOVABLE INSULATION PADS• FLANGE, VALVE AND PUMP COVERS• EQUIPMENT COVERS

THE INFORMATION PRESENTED IS INTENDED AS A SPECIFICATION GUIDE ONLY. MATERIALS SHOULD BE TESTED FOR ITS SUITABILITY IN ANY APPLICATION. USERS SHOULD ALSO FAMILIARIZE THEMSELVES WITH THE MSDS BEFORE HANDLING. NO WARRANTIES ARE EXPRESSED OR IMPLIED AS APPLICATION CONDITIONS ARE BEYOND OUR CONTROL