



7210 C – 5th Street SE  
Calgary, Alberta T2H 2L9

## Technical Data Sheet

Bus: 403-216-3300  
Fax: 403-216-3306  
www.temprotec.com

# TECPRENE® 2401 GLN



ANSI/FM4950 \*  
WELDING CURTAINS

### TEMPERATURE RESISTANCE

BASE FABRIC                    **1000° F**  
COATING                        **225° F**

BASE FABRIC CONTENT                    100% FIBERGLASS YARNS

WEAVE                                        PLAIN

BASE FABRIC WEIGHT                    24.0 oz / yd<sup>2</sup>

BASE FABRIC THICKNESS                0.055"

FINISHED FABRIC WEIGHT                27.0 oz / yd<sup>2</sup>

COUNT                                        WARP: 20                                        FILL: 11

FABRIC FINISH                            COMPOUNDED NEOPRENE RUBBER USED ON ONE SIDE OF THE CLOTH AND THE OTHER SIDE DYED A LIGHT YELLOW (OTHER COLORS AVAILABLE ON REQUEST). USED TO EASE FABRICATION AND INCREASE ABRASION RESISTANCE.

SIZE    40" & 60" x 50 lyds

NOTE: Must be used in a well ventilated area.

**\* NOTE: WELDING PADS AND WELDING BLANKETS MAY ALSO BE USED AS WELDING CURTAINS.**

TecPrene® is a registered trademark of Tempro Tec Inc.

THE INFORMATION PRESENTED IS INTENDED AS A SPECIFICATION GUIDE ONLY. MATERIALS SHOULD BE TESTED FOR ITS SUITABILITY IN ANY APPLICATION. USERS SHOULD ALSO FAMILIARIZE THEMSELVES WITH THE MSDS BEFORE HANDLING. NO WARRANTIES ARE EXPRESSED OR IMPLIED AS APPLICATION CONDITIONS ARE BEYOND OUR CONTROL.

